



INTREPID CONTROL SYSTEMS, INC.

neoRADI/O

Simple, Low Cost CAN I/O

Many lab applications require expanding the capability of your CAN tools to include physical I/O. The neoRADI/O device from Intrepid works with any CAN tool to provide low cost physical I/O. It includes 5 relays, 4 optically isolated digital inputs, and 0-26V analog inputs with 8 bits of resolution. All of these functions are accessed using a dual wire CAN network. When combined with CAN tools from Intrepid Control Systems, neoRADI/O makes controlling physical I/O simple and autonomous. Up to 64 neoRADI/Os can be used on a single CAN network.



Simple Setup: One DIP Switch, One Database (DBC) File

The neoRADI/O device has an internal DIP switch that allows users to configure the CAN baud rate (125k, 250k, 500k or 1Mbit) and the base offset of the CAN ID. Also included is a DBC file which predefines all possible CAN IDs and data values. neoRADI/O is unlike other CAN I/O solutions which require you to have specialized software, drivers, or CAN tools to make them integrate into your current tests.

Hardware Features Overview

- Five (5) Relay Outputs @ 30V Rate 7A @ 250VAC / 28VDC
- Relays with Normal Closed, Common, Normal Open
- Four (4) Optically Isolated (Opto) Digital Inputs @30V
- 15 Software Controlled LEDs for I/O and Relay State Indication
- 64 Configurable CAN IDs
- ISO 11898 Dual Wire CAN Interface
- Supports multiple CAN Baud Rates

Go PC-less for Testing

Combine a neoVI FIRE device, or other neoVI 3G device, to control a group of neoRADI/O boxes. The CoreMini scripting engine, internal to neoVI FIRE, is used to control your test real time and with increased reliability and lower cost than with a PC.

2 CAN messages: One In, One Out

The first CAN message controls the relays and sets up the input reporting. The other message reports the digital and analog inputs. The input reporting can be based on change, time or both. The input reporting is saved to internal device eeprom. For protection, you can enable a timeout for the relay control.

*Specifications subject to change. Please contact Intrepid for the latest information.

Intrepid Control Systems, Inc.

31601 Research Park Drive Madison Heights, MI 48071 USA (ph) +1-586-731-7950 (fax) +1-586-731-2274

www.intrepidcs.com

Rev.08292011